

IMAGING OPTICAL SYSTEM AND OPTICAL APPARATUS USING THE SAME

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to a variable magnification lens which is capable of changing an imaging magnification in accordance with the purpose of use and an optical system which is capable of photographing an image recorded by a film at a magnification most suitable for the film, and to an optical apparatus, such as an image transforming apparatus, using this optical system.

2. Description of Related Art

Imaging optical systems which are designed to be both-side telecentric and to change the imaging magnification have been proposed, for example, by Japanese Patent Kokai No. 2001-27726 and Japanese Patent No. 2731481.

The optical system set forth in Kokai No. 2001-27726 includes, in order from the object side, the first lens unit with positive refractive power, the second lens unit with positive refractive power, the third lens unit with negative refractive power, and the fourth lens unit with positive refractive power. This optical system is thus constructed to be both-side telecentric and to change the imaging magnification.

The optical system set forth in Patent No. 2731481 includes, in order from the object side, the first lens unit with positive refractive power, the second lens unit with negative refractive power, and the third lens unit with positive refractive power. This optical system is thus constructed to be both-side telecentric and to change the imaging magnification while keeping an object-to-image distance constant.

SUMMARY OF THE INVENTION

The imaging optical system of the present invention includes a variable magnifi-

cation optical system comprising, in order from the object side toward the image side, a first lens unit with positive refractive power, a second lens unit with positive refractive power, a third lens unit with negative refractive power, a fourth lens unit with positive refractive power, and an aperture stop interposed between the third lens unit and the fourth lens unit. The variable magnification optical system changes an imaging magnification while keeping an object-to-image distance constant. The imaging magnification is changed by varying spacing between the first lens unit and the second lens unit, spacing between the second lens unit and the third lens unit, and spacing between the third lens unit and the fourth lens unit. When the imaging magnification is changed, the imaging optical system satisfies the following conditions in at least one variable magnification state:

$$|E_n| / L > 0.4$$

$$|E_x| / |L / \beta| > 0.4$$

where E_n is a distance from a first lens surface on the object side of the variable magnification optical system to the entrance pupil of the imaging optical system, L is the object-to-image distance of the imaging optical system, E_x is a distance from the most image-side lens surface of the variable magnification optical system to the exit pupil of the imaging optical system, and β is the magnification of the entire system of the imaging optical system.

The imaging optical system of the present invention preferably satisfies the following conditions:

$$1.0 < \text{MAXFNO} < 8.0$$

$$|\Delta \text{FNO} / \Delta \beta| < 5$$

where MAXFNO is the smallest object-side F-number where the imaging magnification of the imaging optical system is changed, ΔFNO is a difference between the object-side F-number at the minimum magnification and the object-side F-number at the maximum magnification in the entire system of the imaging optical system, and $\Delta \beta$ is a difference between the minimum magnification and the maximum magnifi-

cation in the entire system of the imaging optical system.

The imaging optical system of the present invention preferably satisfies the following condition:

$$0.6 < |(R3f + R3b) / (R3f - R3b)| < 5.0$$

5 where R3f is the radius of curvature of the most object-side surface of the third lens unit and R3b is the radius of curvature of the most image-side surface of the third lens unit.

The imaging optical system of the present invention is preferably constructed so that the most object-side lens of the first lens unit has positive refractive power.

10 The imaging optical system of the present invention is preferably constructed so that the first lens unit includes, in order from the object side, a lens with positive refractive power, a lens with negative refractive power, and a lens with positive refractive power.

15 The imaging optical system of the present invention is preferably constructed so that the third lens unit includes at least two meniscus lenses, each with a convex surface directed toward the object side.

The imaging optical system of the present invention is preferably constructed so that the third lens unit includes two meniscus lenses, each with negative refractive power, and one meniscus lens with positive refractive power.

20 In the present invention, an optical apparatus using the imaging optical system of the present invention is provided.

25 According to the present invention, the imaging optical system in which even when the imaging magnification is changed, the object-to-image distance remains unchanged and the fluctuation of the F-number is minimized, and the optical apparatus using the imaging optical system can be provided.

These and other features and advantages of the present invention will become apparent from the following detailed description of the preferred embodiments when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figs. 1A, 1B, and 1C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of a first embodiment of the imaging optical system according to the present invention;

5 Figs. 2A, 2B, and 2C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the first embodiment;

Figs. 3A, 3B, and 3C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of
10 a second embodiment of the imaging optical system according to the present invention;

Figs. 4A, 4B, and 4C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the second embodiment;

15 Figs. 5A, 5B, and 5C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of a third embodiment of the imaging optical system according to the present invention;

Figs. 6A, 6B, and 6C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the third
20 embodiment;

Figs. 7A, 7B, and 7C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of a fourth embodiment of the imaging optical system according to the present invention;

25 Figs. 8A, 8B, and 8C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the fourth embodiment;

Figs. 9A, 9B, and 9C are sectional views showing optical arrangements, devel-

oped along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of a fifth embodiment of the imaging optical system according to the present invention;

5 Figs. 10A, 10B, and 10C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the fifth embodiment;

Figs. 11A, 11B, and 11C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of a sixth embodiment of the imaging optical system according to the present invention;

10 Figs. 12A, 12B, and 12C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the sixth embodiment;

15 Figs. 13A, 13B, and 13C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of a seventh embodiment of the imaging optical system according to the present invention;

Figs. 14A, 14B, and 14C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the seventh embodiment;

20 Figs. 15A, 15B, and 15C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of an eighth embodiment of the imaging optical system according to the present invention;

25 Figs. 16A, 16B, and 16C are diagrams showing aberration characteristics in focusing at an imaging magnification of 0.4× of the imaging optical system in the eighth embodiment;

Figs. 17A, 17B, and 17C are sectional views showing optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively,

of a ninth embodiment of the imaging optical system according to the present invention;

Figs. 18A, 18B, and 18C are diagrams showing aberration characteristics in focusing at an imaging magnification of $0.4\times$ of the imaging optical system in the ninth embodiment;

Fig. 19 is a conceptual view showing an embodiment of a telecine apparatus using the imaging optical system of the present invention; and

Fig. 20 is a view showing schematically an embodiment of a height measuring apparatus using the imaging optical system of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Before undertaking the description of the embodiments, the function and effect of the present invention will be explained.

In the imaging optical system of the present invention, as described above, the variable magnification optical system includes four lens units with positive, positive, negative, and positive refractive powers. Ahead of (or on the object side of) the stop, the first lens unit with positive refractive power, the second lens unit with positive refractive power, and the third lens unit with negative refractive power are arranged so that the whole of these lens units constitutes a lens system with positive refractive power. The fourth lens unit located behind (or on the image side of) the stop constitutes a lens system with positive refractive power. The aperture stop is interposed between the third lens unit and the fourth lens unit.

The imaging optical system of the present invention is designed to change the imaging magnification while keeping the object-to-image distance constant. That is, the imaging optical system of the present invention is an optical system in which a conjugate length is fixed.

The imaging optical system of the present invention is constructed so that when the imaging magnification is changed, the imaging optical system satisfies the following conditions in at least one variable magnification state and is both-side tele-

centric:

$$|E_n| / L > 0.4 \quad (1)$$

$$|E_x| / |L / \beta| > 0.4 \quad (2)$$

where E_n is a distance from a first lens surface on the object side of the variable magnification optical system to the entrance pupil of the imaging optical system, L is the object-to-image distance of the imaging optical system, E_x is a distance from the most image-side lens surface of the variable magnification optical system to the exit pupil of the imaging optical system, and β is the magnification of the entire system of the imaging optical system.

The imaging optical system of the present invention is constructed so that the stop is located at the focal position of the lens system made up of the first to third lens units lying on the object side of the stop. By this arrangement, the entrance pupil which is the image of the stop is projected at infinity. As a result, the imaging optical system of the present invention constitutes an object-side telecentric optical system.

Further, the imaging optical system of the present invention is constructed so that the stop is located at the focal position of the lens system of the fourth lens unit lying on the image side of the stop. By this arrangement, the exit pupil which is the image of the stop is projected at infinity. As a result, the imaging optical system of the present invention also constitutes an image-side telecentric optical system.

In the imaging optical system of the present invention constructed as mentioned above, the role of a multi-variator is allotted to each of the second lens unit with positive refractive power and the third lens unit with negative refractive power. Whereby, a synthesized focal length of the first to third lens units located on the object side of the stop can be changed.

Still further, the imaging optical system of the present invention is constructed so that the stop is interposed between the third lens unit and the fourth lens unit. The fourth lens unit located on the image side of the stop has no variable magnifica-

tion function. Even when the imaging magnification is changed, the shift of the position of the stop is suppressed as far as possible so that the position of the stop remains practically unchanged. An arrangement is thus made such that the stop is always located in the proximity of the focal position of the fourth lens unit,, and thereby the imaging optical system is capable of changing the imaging magnification while maintaining the telecentric characteristic and the F-number on the exit side.

However, in order to maintain the object-side telecentric characteristic and fix the conjugate length while keeping the F-number constant when the imaging magnification is changed, it is necessary to satisfy conditions described below. First, even in the magnification change, the stop must be located at the synthesized focal position of the first to third lens units lying on the object side of the stop. Second, even in the magnification change, a distance from an object surface to a stop surface must be kept nearly constant.

In the lens arrangement of positive, negative, and positive refractive powers, if the first lens unit is divided into two lens units with positive and negative refractive powers, the balance between the refractive powers will be destroyed. Consequently, chromatic aberration of magnification and distortion will be increased. As in the present invention, when the first lens unit is divided into two lens units with positive and positive refractive powers and the optical system is constructed with four lens units with positive, positive, negative, and positive refractive powers, the amount of the production of aberration can be minimized.

In the both-side telecentric optical system, even when the magnification is changed, an off-axis ray of light at the position of the stop is nearly parallel to the optical axis. On the image side of the stop, only the fourth lens unit is located, and it is not moved, thus making the focal length constant. Hence, when the magnification is changed, the fluctuation of the image-side F-number is minimized, and it is not necessary to adjust the brightness of a camera even in this case.

When the object-side telecentric optical system is constructed like the imaging

optical system of the present invention, the following advantages are obtained. To explain this, a telecine apparatus (a motion picture film scanner) is cited as an example. The telecine apparatus is adapted to digitize the motion picture film. The telecine apparatus is constructed so that the film is illuminated by an illumination optical system and an image is formed by a solid-state image sensor, such as a CCD, through the imaging optical system.

However, when the imaging optical system of the telecine apparatus is constructed to be object-side telecentric like the imaging optical system of the present invention, matching of the pupil of the illumination system with the imaging system is facilitated, and a loss of the amount of light is reduced. Moreover, a change in magnification on an image plane, caused by the disturbance of flatness of the film, can be kept to a minimum.

When the image-side telecentric optical system is constructed like the imaging optical system of the present invention, the following advantages are obtained. To explain this, a so-called multi-imager camera using image sensors in accordance with colors, such as RGB, is cited as an example. In this multi-imager camera, a color separation prism is generally used. This prism has a separation interference film splitting light in accordance with wavelength, namely a dichroic film, on its interface. If the exit pupil is located close to the image plane, the angle of incidence where a chief ray is incident on the interference film will be changed in accordance with the position of an image point on the image. Consequently, the optical path length of film thickness is changed and a color separation characteristic is varied in accordance with a field angle, bringing about different color reproducibility, that is, causing color shading.

However, when the imaging optical system of the multi-imager camera is constructed to be image-side telecentric like the imaging optical system of the present invention, color shading can be suppressed.

Here, for example, it is assumed that the solid-image sensor, such as the CCD, is

placed on the image side of the color separation prism. If the exit pupil is located close to the image plane, the chief ray is obliquely incident on a pixel. Thus, off-axis incident light is chiefly blocked by the structure of the CCD to decrease the amount of light, and light other than that to enter an original light-receiving section is incident. This brings about a state where a signal other than original information is output. That is, shading is caused.

However, when the image-side telecentric optical system is constructed like the imaging optical system of the present invention, shading can be suppressed.

The imaging optical system of the present invention is also constructed as the both-side telecentric optical system. Consequently, the imaging magnification can be practically determined by the ratio between the focal length of the lens units located on the object side of the stop and the focal length of the lens unit located on the image side of the stop.

Spacings between individual lens units located on the object side of the stop are changed so that the focal length of the lens units on the object side of the stop is varied. Whereby, the imaging magnification can be changed.

In the imaging optical system of the present invention, the first lens unit has the positive refractive power, and the entrance pupil which is the image of the stop is projected at infinity. In doing so, a chief ray on the object side of the first lens unit is refracted parallel to the optical axis and thereby the object-side telecentric optical system can be realized.

In the imaging optical system of the present invention, the second lens unit has the positive refractive power and the third lens unit has the negative refractive power. By changing the spacing between the second lens unit and the third lens unit, the synthesized focal length of the second and third lens units is varied. That is, the second and third lens units are designed to function as a multi-variator. Thus, the second and third lens units are moved, and thereby the magnification can be optimally adjusted to the size of an object.

When the third lens unit is designed to have the negative refractive power like the imaging optical system of the present invention, the Petzval sum is increased and an optical system which is free of curvature of field can be realized.

5 The imaging optical system of the present invention is also constructed so that the positive refractive power is imparted to the fourth lens unit and the exit pupil which is the image of the stop is projected at infinity. Thus, the chief ray on the image side of the fourth lens unit is rendered parallel to the optical axis, and thereby the image-side telecentric optical system can be realized.

10 When the imaging optical system of the present invention provided with the variable magnification function, mentioned above, is used to construct an optical apparatus, the following advantages are obtained. To explain this, for example, the telecine apparatus is cited as described above. The telecine apparatus, in which a video camera is attached to a film photographing device, is constructed so that the film image is converted into a video signal, which is digitized.

15 On the other hand, motion picture films have a plurality of standards, and the size of the image section of the film varies with each standard. For example, a 35 mm standard film measures 16 (height) \times 21.95 (width) mm and a European wide film measures 11.9 \times 21.95 mm. In this way, the aspect ratio of the film varies according to the film standard. The dimension of the imaging surface of the CCD, for example, in a 2/3" CCD solid-state image sensor, is 5.4 \times 9.6 mm. In order to photograph an image through superfine pixels, it is desirable to acquire image information relative to the entire CCD imaging area. For this purpose, it becomes necessary to change the imaging magnification in accordance with the film standard.

20 However, when the imaging optical system of the present invention is used to construct the optical apparatus, the films of various standards can be digitized, for example, in the telecine apparatus. In this case, even when the imaging magnification is changed, the conjugate length remains unchanged, and the magnification can be varied with little fluctuation in image-side F-number.

For example, when the imaging optical system of the present invention is used to construct the multi-imager camera, color shading caused by the color separation prism and shading of the CCD camera can be suppressed. Moreover, the imaging magnification can be changed, without moving the camera, in accordance with the film standard and the size of the object, and even when the magnification is changed, the adjustment of brightness is unnecessary.

In the imaging optical system of the present invention, in order to obtain further both-side telecentricity, it is favorable that when imaging magnification is changed, the imaging optical system satisfies the following conditions, instead of Conditions (1) and (2), in at least one variable magnification state:

$$|E_n| / L > 0.8 \quad (1')$$

$$|E_x| / |L / \beta| > 0.8 \quad (2')$$

It is more favorable to satisfy the following conditions:

$$|E_n| / L > 1.6 \quad (1'')$$

$$|E_x| / |L / \beta| > 1.6 \quad (2'')$$

In the imaging optical system of the present invention, the F-number is defined by the following conditions:

$$1.0 < \text{MAXFNO} < 8.0 \quad (3)$$

$$|\Delta \text{FNO} / \Delta \beta| < 5 \quad (4)$$

where MAXFNO is the smallest object-side F-number where the imaging magnification of the imaging optical system is changed, ΔFNO is a difference between the object-side F-number at the minimum magnification and the object-side F-number at the maximum magnification in the entire system of the imaging optical system, and $\Delta \beta$ is a difference between the minimum magnification and the maximum magnification in the entire system of the imaging optical system.

Also, the F-number refers to an amount expressing the brightness of the optical system. As the value of the F-number becomes small, a brighter optical system is obtained.

If the F-number is extremely small, the number of lenses must be increased in order to correct aberration. This causes the problem that the overall length of the optical system is increased. On the other hand, an extremely large F-number is not suitable for motion picture photography because of shortage in the amount of light.

5 However, when the optical system satisfies Condition (3), the F-number is neither extremely small nor large. The above problems that the overall length of the optical system is increased and the F-number is not suitable for motion picture photography can thus be obviated.

10 If the value of $|\Delta FNO / \Delta \beta|$ is extremely large, the fluctuation of the image-side F-number becomes remarkable in the magnification change. As a result, the brightness of the camera must be adjusted. However, when Condition (4) is satisfied, there is no need to adjust the brightness of the camera.

It is desirable to satisfy the following conditions:

$$2.0 < MAXFNO < 5.6 \quad (3')$$

15 $|\Delta FNO / \Delta \beta| < 3 \quad (4')$

It is more desirable to satisfy the following conditions:

$$3.0 < MAXFNO < 4.0 \quad (3'')$$

$$|\Delta FNO / \Delta \beta| < 1 \quad (4'')$$

20 In the imaging optical system of the present invention, it is desirable that the most object-side lens of the first lens unit has the positive refractive power. When the most object-side lens of the first lens unit is constructed as the positive lens, an off-axis beam of light can be lowered and thus aberration becomes small.

25 In the imaging optical system of the present invention, it is desirable that the first lens unit includes, in order from the object side, positive, negative, and positive lenses. When the first lens unit is constructed with the positive, negative, and positive lenses, chromatic aberration of magnification and off-axis chromatic aberration can be corrected.

In the imaging optical system of the present invention, it is desirable to satisfy a

condition described below. When this condition is satisfied, the fluctuation of off-axis aberration can be kept to a minimum.

$$0.6 < |(R3f + R3b) / (R3f - R3b)| < 5.0 \quad (5)$$

where $|(R3f + R3b) / (R3f - R3b)|$ is a virtual shape factor, R3f is the radius of curvature of the most object-side surface of the third lens unit and R3b is the radius of curvature of the most image-side surface of the third lens unit.

Beyond the upper limit of the virtual shape factor, the radius of curvature of the most object-side surface of the third lens unit approximates that of the most image-side surface of the third lens unit. As such, the refractive power of the third lens unit becomes extremely weak. Consequently, when the imaging magnification is changed, the amount of movement of the third lens unit must be increased. When the amount of movement of the third lens unit is large, the ray height of off-axis light incident on the third lens unit fluctuates. Thus, the fluctuation of off-axis aberration becomes pronounced. Below the lower limit of the virtual shape factor, the refractive power of the third lens unit becomes extremely strong. As a result, the angle of incidence of the off-axis beam on the third lens unit is increased, and the fluctuation of off-axis aberration caused by the movement of the third lens unit becomes heavy.

However, when Condition (5) is satisfied, the refractive power of the third lens unit is neither extremely high nor low, and the above problem that the fluctuation of off-axis aberration is heavy can be obviated.

It is desirable to satisfy the following condition:

$$1.2 < |(R3f + R3b) / (R3f - R3b)| < 3.5 \quad (5')$$

It is more desirable to satisfy the following condition:

$$2.0 < |(R3f + R3b) / (R3f - R3b)| < 3.0 \quad (5'')$$

In the imaging optical system of the present invention, it is desirable that the third lens unit has at least two meniscus lenses, each with a convex surface directed toward the object side. It is more desirable that the third lens unit has at least three meniscus lenses. More specifically, it is desirable that the third lens unit, for exam-

ple, has two negative meniscus lenses, each with a convex surface directed toward the object side, and one positive meniscus lens with a convex surface directed toward the object side. Since the third lens unit is located close to the stop, off-axis rays are incident on the lenses of the third lens unit at almost the same angle, irrespective of the angle of view.

However, the meniscus lens in which a convex surface is directed toward the object side, namely the object-side surface has the positive refractive power, has nearly minimum deflection angles with respect to on- and off-axis light beams at individual angles of view, and hence the production of aberration can be prevented.

In accordance with the drawings, the embodiments of the present invention will be described below.

First embodiment

Figs. 1A, 1B, and 1C show optical arrangements, developed along the optical axis, at magnifications of $0.3\times$, $0.4\times$, and $0.5\times$, respectively, of the first embodiment of the imaging optical system according to the present invention. Figs. 2A, 2B, and 2C show aberration characteristics in focusing at an imaging magnification of $0.4\times$ of the imaging optical system in the first embodiment.

The imaging optical system of the first embodiment has a variable magnification optical system Z. In Fig. 1A, reference symbol P represents a prism, CG represents a cover glass, and I represents an imaging surface.

The variable magnification optical system Z comprises, in order from the object side toward the image side, a first lens unit G1 with positive refractive power, a second lens unit G2 with positive refractive power, a third lens unit G3 with negative refractive power, an aperture stop S, and a fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, a biconvex lens $L1_1$, a biconcave lens $L1_2$, and a biconvex lens $L1_3$.

The second lens unit G2 includes, in order from the object side, a negative me-

niscus lens L2₁ with a convex surface directed toward the object side, a biconvex lens L2₂, a negative meniscus lens L2₃ with a concave surface directed toward the object side, and a biconvex lens L2₄.

The third lens unit G3 includes a positive meniscus lens L3₁ with a convex surface directed toward the object side, a negative meniscus lens L3₂ with a convex surface directed toward the object side, and a negative meniscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes a cemented doublet of a biconcave lens L4₁ and a biconvex lens L4₂, a biconcave lens L4₃, a biconvex lens L4₄, a biconvex lens L4₅, and a biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of an infinite object point, the first lens unit G1, after being moved once toward the object side, is moved toward the image side, the second lens unit G2 is moved toward the object side, the third lens unit G3 is moved toward the image side together with the stop S, and the fourth lens unit G4 is moved toward the image side so that spacing between the third and fourth lens units G3 and G4 is slightly widened. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the first embodiment are shown below. In the numerical data, r_0 , r_1 , r_2 , ... denote radii of curvature of surfaces of individual optical members shown in this order from the object side; d_0 , d_1 , d_2 , ... denote thicknesses (mm) of individual optical members or air spacings between them; n_{e1} , n_{e2} , ... denote refractive indices of individual optical members at the e line; ν_{e1} , ν_{e2} , ... denote Abbe's numbers of individual optical members at the e line. These symbols are also used for the numerical data of other embodiments to be described later.

Numerical data 1

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

	$d_0 = 50.000$		
	$r_1 = \infty$ (object surface)		
	$d_1 = D1$		
	$r_2 = 189.5313$		
5	$d_2 = 7.308$	$n_{e2} = 1.48915$	$v_{e2} = 70.04$
	$r_3 = -117.0877$		
	$d_3 = 10.588$		
	$r_4 = -6124.8097$		
	$d_4 = 6.910$	$n_{e4} = 1.61639$	$v_{e4} = 44.15$
10	$r_5 = 67.5133$		
	$d_5 = 12.028$		
	$r_6 = 88.2299$		
	$d_6 = 8.685$	$n_{e6} = 1.43985$	$v_{e6} = 94.53$
	$r_7 = -425.3119$		
15	$d_7 = D7$		
	$r_8 = 148.1127$		
	$d_8 = 6.000$	$n_{e8} = 1.61639$	$v_{e8} = 44.15$
	$r_9 = 64.7754$		
	$d_9 = 5.355$		
20	$r_{10} = 88.2208$		
	$d_{10} = 8.016$	$n_{e10} = 1.43985$	$v_{e10} = 94.53$
	$r_{11} = -81.9368$		
	$d_{11} = 1.062$		
	$r_{12} = -69.6148$		
25	$d_{12} = 7.000$	$n_{e12} = 1.61639$	$v_{e12} = 44.15$
	$r_{13} = -171.6506$		
	$d_{13} = 17.627$		
	$r_{14} = 210.1703$		

		$d_{14} = 6.814$	$n_{e14} = 1.43985$	$\nu_{e14} = 94.53$
	$r_{15} =$	-82.3361		
		$d_{15} = D15$		
	$r_{16} =$	40.6305		
5		$d_{16} = 4.323$	$n_{e16} = 1.69417$	$\nu_{e16} = 30.83$
	$r_{17} =$	250.0598		
		$d_{17} = 0.300$		
	$r_{18} =$	25.0517		
		$d_{18} = 9.360$	$n_{e18} = 1.72538$	$\nu_{e18} = 34.47$
10	$r_{19} =$	21.5375		
		$d_{19} = 1.156$		
	$r_{20} =$	41.2143		
		$d_{20} = 2.000$	$n_{e20} = 1.72538$	$\nu_{e20} = 34.47$
	$r_{21} =$	15.8016		
15		$d_{21} = 2.560$		
	$r_{22} =$	∞ (aperture stop)		
		$d_{22} = D22$		
	$r_{23} =$	-29.2488		
		$d_{23} = 2.000$	$n_{e23} = 1.61669$	$\nu_{e23} = 44.02$
20	$r_{24} =$	23.4936		
		$d_{24} = 7.647$	$n_{e24} = 1.48915$	$\nu_{e24} = 70.04$
	$r_{25} =$	-17.8845		
		$d_{25} = 3.043$		
	$r_{26} =$	-13.7038		
25		$d_{26} = 1.417$	$n_{e26} = 1.61639$	$\nu_{e26} = 44.15$
	$r_{27} =$	89.8893		
		$d_{27} = 4.829$		
	$r_{28} =$	707.1568		

	$d_{28} = 8.564$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$
	$r_{29} = -18.1649$		
	$d_{29} = 0.325$		
	$r_{30} = 69.4722$		
5	$d_{30} = 5.111$	$n_{e30} = 1.43985$	$\nu_{e30} = 94.53$
	$r_{31} = -90.8646$		
	$d_{31} = 0.300$		
	$r_{32} = 62.9985$		
	$d_{32} = 4.778$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$
10	$r_{33} = -179.4454$		
	$d_{33} = D33$		
	$r_{34} = \infty$		
	$d_{34} = 33.000$	$n_{e34} = 1.61173$	$\nu_{e34} = 46.30$
	$r_{35} = \infty$		
15	$d_{35} = 13.200$	$n_{e35} = 1.51825$	$\nu_{e35} = 63.93$
	$r_{36} = \infty$		
	$d_{36} = 0.500$		
	$r_{37} = \infty$ (imaging surface)		
	$d_{37} = 0.000$		

20 Zoom data

	0.3×	0.4×	0.5×
D1	39.880	37.812	44.358
D7	109.204	77.238	48.939
D15	3.000	37.903	60.723
25 D22	3.552	4.754	6.263
D33	21.051	18.980	16.405

Parameters of conditions

Magnification : β	0.3×	0.4×	0.5×
-------------------------	------	------	------

	Entrance pupil position : En	1160.856	20252.775	-1133.552
	Object-to-image distance : L	428.492	428.492	428.492
	En / L	2.709	47.265	2.645
	Exit pupil position : Ex	-352.468	-578.834	-1818.976
5	Ex / L / β	0.247	0.540	2.123
	F-number : FNO	3.500	3.536	3.598
	FNO fluctuation : Δ FNO		0.098	
	Δ FNO / $\Delta\beta$		0.490	
	Object-side radius of curvature : R3f		40.630	
10	Image-side radius of curvature : R3b		15.802	
	(R3f + R3b) / (R3f - R3b)		2.273	

Second embodiment

Figs. 3A, 3B, and 3C show optical arrangements, developed along the optical axis, at magnifications of 0.3 \times , 0.4 \times , and 0.5 \times , respectively, of the second embodiment of the imaging optical system according to the present invention. Figs. 4A, 4B, and 4C show aberration characteristics in focusing at a magnification of 0.4 \times of the imaging optical system in the second embodiment.

The imaging optical system of the second embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, the biconvex lens L1₁, a negative meniscus lens L1₂' with a convex surface directed toward the object side, and the biconvex lens L1₃.

The second lens unit G2, in order from the object side, the negative meniscus

lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂, the negative meniscus lens L2₃ with a concave surface directed toward the object side, and the biconvex lens L2₄.

The third lens unit G3 includes the positive meniscus lens L3₁ with a convex surface directed toward the object side, the negative meniscus lens L3₂ with a convex surface directed toward the object side, and the negative meniscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes the cemented doublet of the biconcave lens L4₁ and the biconvex lens L4₂, the biconcave lens L4₃, the biconvex lens L4₄, the biconvex lens L4₅, and the biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1, after being moved once toward the object side, is moved toward the image side, the second lens unit G2 is moved toward the object side, the third lens unit G3 remains fixed together with the stop S, and the fourth lens unit G4 is moved toward the image side so that the spacing between the third and fourth lens units G3 and G4 is slightly widened. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the second embodiment are shown below.

Numerical data 2

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

$$d_0 = 50.000$$

$$r_1 = \infty \text{ (object surface)}$$

$$d_1 = D1$$

$$r_2 = 172.4277$$

$$d_2 = 6.648 \quad n_{e2} = 1.48915 \quad \nu_{e2} = 70.04$$

$$r_3 = -112.2625$$

	$d_3 = 7.313$			
	$r_4 = 1492.6672$			
	$d_4 = 7.985$	$n_{e4} = 1.61639$	$\nu_{e4} = 44.15$	
	$r_5 = 62.4069$			
5	$d_5 = 12.125$			
	$r_6 = 79.8565$			
	$d_6 = 9.415$	$n_{e6} = 1.43985$	$\nu_{e6} = 94.53$	
	$r_7 = -1585.7009$			
	$d_7 = D7$			
10	$r_8 = 151.8708$			
	$d_8 = 6.000$	$n_{e8} = 1.61639$	$\nu_{e8} = 44.15$	
	$r_9 = 64.4718$			
	$d_9 = 5.384$			
	$r_{10} = 86.7203$			
15	$d_{10} = 8.163$	$n_{e10} = 1.43985$	$\nu_{e10} = 94.53$	
	$r_{11} = -80.8037$			
	$d_{11} = 1.049$			
	$r_{12} = -68.7719$			
	$d_{12} = 6.410$	$n_{e12} = 1.61639$	$\nu_{e12} = 44.15$	
20	$r_{13} = -178.7270$			
	$d_{13} = 16.603$			
	$r_{14} = 219.0646$			
	$d_{14} = 6.722$	$n_{e14} = 1.43985$	$\nu_{e14} = 94.53$	
	$r_{15} = -81.1984$			
25	$d_{15} = D15$			
	$r_{16} = 40.1465$			
	$d_{16} = 4.375$	$n_{e16} = 1.69417$	$\nu_{e16} = 30.83$	
	$r_{17} = 229.4681$			

		$d_{17} = 0.300$		
	$r_{18} =$	24.8118		
		$d_{18} = 9.366$	$n_{e18} = 1.72538$	$\nu_{e18} = 34.47$
	$r_{19} =$	21.1952		
5		$d_{19} = 1.169$		
	$r_{20} =$	40.9998		
		$d_{20} = 2.000$	$n_{e20} = 1.72538$	$\nu_{e20} = 34.47$
	$r_{21} =$	15.9793		
		$d_{21} = 2.555$		
10	$r_{22} =$	∞ (aperture stop)		
		$d_{22} = D22$		
	$r_{23} =$	-29.1565		
		$d_{23} = 2.000$	$n_{e23} = 1.61669$	$\nu_{e23} = 44.02$
	$r_{24} =$	23.6864		
15		$d_{24} = 7.373$	$n_{e24} = 1.48915$	$\nu_{e24} = 70.04$
	$r_{25} =$	-18.0561		
		$d_{25} = 3.435$		
	$r_{26} =$	-13.7966		
		$d_{26} = 1.355$	$n_{e26} = 1.61639$	$\nu_{e26} = 44.15$
20	$r_{27} =$	84.7189		
		$d_{27} = 4.778$		
	$r_{28} =$	547.3608		
		$d_{28} = 8.544$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$
	$r_{29} =$	-18.0837		
25		$d_{29} = 0.300$		
	$r_{30} =$	70.0296		
		$d_{30} = 5.063$	$n_{e30} = 1.43985$	$\nu_{e30} = 94.53$
	$r_{31} =$	-93.9274		

	$d_{31} = 0.388$		
	$r_{32} = 58.3720$		
	$d_{32} = 4.869$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$
	$r_{33} = -203.9907$		
5	$d_{33} = D33$		
	$r_{34} = \infty$		
	$d_{34} = 33.000$	$n_{e34} = 1.61173$	$\nu_{e34} = 46.30$
	$r_{35} = \infty$		
	$d_{35} = 13.200$	$n_{e35} = 1.51825$	$\nu_{e35} = 63.93$
10	$r_{36} = \infty$		
	$d_{36} = 0.500$		
	$r_{37} = \infty$ (imaging surface)		
	$d_{37} = 0.000$		

Zoom data

15		0.3×	0.4×	0.5×
	D1	43.904	39.311	43.788
	D7	110.381	79.183	50.950
	D15	3.089	38.880	62.637
	D22	3.559	5.250	7.195
20	D33	20.639	18.949	17.003

Parameters of conditions

	Magnification : β	0.3×	0.4×	0.5×
	Entrance pupil position : En	1124.667	16516.516	-1141.823
	Object-to-image distance : L	429.959	429.959	429.959
25	$ En / L$	2.616	38.414	2.656
	Exit pupil position : Ex	-351.154	-741.700	24496.963
	$ Ex / L / \beta $	0.245	0.690	28.488
	F-number : FNO	3.500	3.560	3.646

FNO fluctuation : ΔFNO	0.146
$ \Delta FNO / \Delta \beta $	0.729
Object-side radius of curvature : $R3f$	38.452
Image-side radius of curvature : $R3b$	17.589
$ (R3f + R3b) / (R3f - R3b) $	2.686

Third embodiment

Figs. 5A, 5B, and 5C show optical arrangements, developed along the optical axis, at magnifications of 0.3 \times , 0.4 \times , and 0.5 \times , respectively, of the third embodiment of the imaging optical system according to the present invention. Figs. 6A, 6B, and 6C show aberration characteristics in focusing at a magnification of 0.4 \times of the imaging optical system in the third embodiment.

The imaging optical system of the third embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, the biconvex lens L1₁, the negative meniscus lens L1₂' with a convex surface directed toward the object side, and a positive meniscus lens L1₃' with a convex surface directed toward the object side.

The second lens unit G2, in order from the object side, the negative meniscus lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂, the negative meniscus lens L2₃ with a concave surface directed toward the object side, and the biconvex lens L2₄.

The third lens unit G3 includes the positive meniscus lens L3₁ with a convex surface directed toward the object side, the negative meniscus lens L3₂ with a convex

surface directed toward the object side, and the negative meniscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes the cemented doublet of the biconcave lens L4₁ and the biconvex lens L4₂, the biconcave lens L4₃, the biconvex lens L4₄, the biconvex lens L4₅, and the biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1, after being moved once toward the object side, is moved toward the image side, the second lens unit G2 is moved toward the object side, the third lens unit G3 is moved toward the object side together with the stop S so that the spacing between the third and fourth lens units G3 and G4 is slightly widened, and the fourth lens unit G4 remains fixed. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the third embodiment are shown below.

Numerical data 3

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

$$d_0 = 50.000$$

$$r_1 = \infty \text{ (object surface)}$$

$$d_1 = D1$$

$$r_2 = 67.5689$$

$$d_2 = 7.816 \quad n_{c2} = 1.48915 \quad \nu_{c2} = 70.04$$

$$r_3 = -335.3716$$

$$d_3 = 0.300$$

$$r_4 = 140.6380$$

$$d_4 = 6.025 \quad n_{c4} = 1.61639 \quad \nu_{c4} = 44.15$$

$$r_5 = 45.2535$$

$$d_5 = 8.810$$

	$r_6 = 57.6476$			
	$d_6 = 11.963$	$n_{c6} = 1.43985$	$\nu_{c6} = 94.53$	
	$r_7 = 109.0130$			
	$d_7 = D7$			
5	$r_8 = 140.9050$			
	$d_8 = 6.209$	$n_{c8} = 1.61639$	$\nu_{c8} = 44.15$	
	$r_9 = 59.1517$			
	$d_9 = 5.421$			
	$r_{10} = 89.7738$			
10	$d_{10} = 7.460$	$n_{c10} = 1.43985$	$\nu_{c10} = 94.53$	
	$r_{11} = -74.4487$			
	$d_{11} = 1.335$			
	$r_{12} = -57.6329$			
	$d_{12} = 7.000$	$n_{c12} = 1.61639$	$\nu_{c12} = 44.15$	
15	$r_{13} = -145.4391$			
	$d_{13} = 15.344$			
	$r_{14} = 312.0611$			
	$d_{14} = 8.089$	$n_{c14} = 1.43985$	$\nu_{c14} = 94.53$	
	$r_{15} = -66.7614$			
20	$d_{15} = D15$			
	$r_{16} = 42.2336$			
	$d_{16} = 4.331$	$n_{c16} = 1.69417$	$\nu_{c16} = 30.83$	
	$r_{17} = 254.0344$			
	$d_{17} = 0.300$			
25	$r_{18} = 24.1640$			
	$d_{18} = 9.326$	$n_{c18} = 1.72538$	$\nu_{c18} = 34.47$	
	$r_{19} = 20.0169$			
	$d_{19} = 1.206$			

	$r_{20} = 36.3821$			
	$d_{20} = 2.000$	$n_{e20} = 1.72538$	$\nu_{e20} = 34.47$	
	$r_{21} = 16.7574$			
	$d_{21} = 2.601$			
5	$r_{22} = \infty$ (aperture stop)			
	$d_{22} = D22$			
	$r_{23} = -26.7471$			
	$d_{23} = 2.030$	$n_{e23} = 1.61669$	$\nu_{e23} = 44.02$	
	$r_{24} = 24.0157$			
10	$d_{24} = 5.463$	$n_{e24} = 1.48915$	$\nu_{e24} = 70.04$	
	$r_{25} = -17.6590$			
	$d_{25} = 4.328$			
	$r_{26} = -13.4729$			
	$d_{26} = 1.058$	$n_{e26} = 1.61639$	$\nu_{e26} = 44.15$	
15	$r_{27} = 93.0104$			
	$d_{27} = 4.726$			
	$r_{28} = 913.0291$			
	$d_{28} = 8.540$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$	
	$r_{29} = -17.8834$			
20	$d_{29} = 0.300$			
	$r_{30} = 81.9603$			
	$d_{30} = 6.985$	$n_{e30} = 1.43985$	$\nu_{e30} = 94.53$	
	$r_{31} = -64.2115$			
	$d_{31} = 3.523$			
25	$r_{32} = 60.0466$			
	$d_{32} = 6.110$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$	
	$r_{33} = -318.5459$			
	$d_{33} = 19.314$			

	$r_{34} = \infty$			
	$d_{34} = 33.000$	$n_{e34} = 1.61173$	$v_{e34} = 46.30$	
	$r_{35} = \infty$			
	$d_{35} = 13.200$	$n_{e35} = 1.51825$	$v_{e35} = 63.93$	
5	$r_{36} = \infty$			
	$d_{36} = 0.500$			
	$r_{37} = \infty$ (imaging surface)			
	$d_{37} = 0.000$			
	Zoom data			
10		0.3×	0.4×	0.5×
	D1	50.134	38.319	43.946
	D7	107.947	77.883	43.657
	D15	3.000	42.757	69.242
	D22	3.638	5.759	7.874
15	Parameters of conditions			
	Magnification : β	0.3×	0.4×	0.5×
	Entrance pupil position : En	1271.479	-18393.929	-1095.982
	Object-to-image distance : L	429.334	429.334	429.334
	$ En / L$	2.962	42.843	2.553
20	Exit pupil position : Ex	-362.746	-906.100	4824.866
	$ Ex / L / \beta $	0.253	0.844	5.619
	F-number : FNO	3.500	3.593	3.687
	FNO fluctuation : ΔFNO		0.187	
	$ \Delta FNO / \Delta \beta $		0.935	
25	Object-side radius of curvature : R3f		42.234	
	Image-side radius of curvature : R3b		16.757	
	$ (R3f + R3b) / (R3f - R3b) $		2.316	

Fourth embodiment

Figs. 7A, 7B, and 7C show optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of the fourth embodiment of the imaging optical system according to the present invention. Figs. 8A, 8B, and 8C show aberration characteristics in focusing at a magnification of 0.4× of the imaging optical system in the fourth embodiment.

The imaging optical system of the fourth embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, the biconvex lens L1₁, the negative meniscus lens L1₂' with a convex surface directed toward the object side, and the positive meniscus lens L1₃' with a convex surface directed toward the object side.

The second lens unit G2, in order from the object side, the negative meniscus lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂, the negative meniscus lens L2₃ with a concave surface directed toward the object side, and the biconvex lens L2₄.

The third lens unit G3 includes the positive meniscus lens L3₁ with a convex surface directed toward the object side, the negative meniscus lens L3₂ with a convex surface directed toward the object side, and the negative meniscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes the cemented doublet of the biconcave lens L4₁ and the biconvex lens L4₂, the biconcave lens L4₃, the biconvex lens L4₄, the biconvex lens L4₅, and the biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite

object point, the first lens unit G1 is moved toward the image side, the second lens unit G2 is moved toward the object side, the third lens unit G3 is moved toward the image side, and the fourth lens unit G4 is moved toward the image side together with the stop S so that the spacing between the third and fourth lens units G3 and G4 is slightly widened. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the fourth embodiment are shown below.

Numerical data 4

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

$$d_0 = 50.000$$

$$r_1 = \infty \text{ (object surface)}$$

$$d_1 = D1$$

$$r_2 = 107.8560$$

$$d_2 = 7.337 \quad n_{e2} = 1.48915 \quad \nu_{e2} = 70.04$$

$$r_3 = -119.7849$$

$$d_3 = 3.971$$

$$r_4 = 454.1088$$

$$d_4 = 7.857 \quad n_{e4} = 1.61639 \quad \nu_{e4} = 44.15$$

$$r_5 = 49.9355$$

$$d_5 = 12.309$$

$$r_6 = 64.2291$$

$$d_6 = 6.018 \quad n_{e6} = 1.43985 \quad \nu_{e6} = 94.53$$

$$r_7 = 300.8668$$

$$d_7 = D7$$

$$r_8 = 126.3256$$

$$d_8 = 6.000 \quad n_{e8} = 1.61639 \quad \nu_{e8} = 44.15$$

	$r_9 = 56.4062$			
	$d_9 = 6.775$			
	$r_{10} = 81.4055$			
	$d_{10} = 8.793$	$n_{e10} = 1.43985$	$\nu_{e10} = 94.53$	
5	$r_{11} = -83.1434$			
	$d_{11} = 1.494$			
	$r_{12} = -63.8486$			
	$d_{12} = 7.000$	$n_{e12} = 1.61639$	$\nu_{e12} = 44.15$	
	$r_{13} = -133.7944$			
10	$d_{13} = 15.757$			
	$r_{14} = 330.3809$			
	$d_{14} = 7.640$	$n_{e14} = 1.43985$	$\nu_{e14} = 94.53$	
	$r_{15} = -69.3107$			
	$d_{15} = D15$			
15	$r_{16} = 40.1299$			
	$d_{16} = 4.652$	$n_{e16} = 1.69417$	$\nu_{e16} = 30.83$	
	$r_{17} = 187.3566$			
	$d_{17} = 0.300$			
	$r_{18} = 24.6796$			
20	$d_{18} = 9.359$	$n_{e18} = 1.72538$	$\nu_{e18} = 34.47$	
	$r_{19} = 20.3802$			
	$d_{19} = 1.377$			
	$r_{20} = 39.2697$			
	$d_{20} = 2.000$	$n_{e20} = 1.72538$	$\nu_{e20} = 34.47$	
25	$r_{21} = 16.0804$			
	$d_{21} = D21$			
	$r_{22} = \infty$ (aperture stop)			
	$d_{22} = 3.575$			

	$r_{23} = -30.0984$			
	$d_{23} = 2.000$	$n_{e23} = 1.61669$	$\nu_{e23} = 44.02$	
	$r_{24} = 23.9795$			
	$d_{24} = 8.757$	$n_{e24} = 1.48915$	$\nu_{e24} = 70.04$	
5	$r_{25} = -18.9682$			
	$d_{25} = 3.837$			
	$r_{26} = -14.1963$			
	$d_{26} = 0.817$	$n_{e26} = 1.61639$	$\nu_{e26} = 44.15$	
	$r_{27} = 101.4717$			
10	$d_{27} = 4.565$			
	$r_{28} = 1012.5847$			
	$d_{28} = 8.419$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$	
	$r_{29} = -18.1103$			
	$d_{29} = 0.629$			
15	$r_{30} = 69.9749$			
	$d_{30} = 4.880$	$n_{e30} = 1.43985$	$\nu_{e30} = 94.53$	
	$r_{31} = -123.8898$			
	$d_{31} = 0.928$			
	$r_{32} = 61.1846$			
20	$d_{32} = 4.997$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$	
	$r_{33} = -136.6736$			
	$d_{33} = D33$			
	$r_{34} = \infty$			
	$d_{34} = 33.000$	$n_{e34} = 1.61173$	$\nu_{e34} = 46.30$	
25	$r_{35} = \infty$			
	$d_{35} = 13.200$	$n_{e35} = 1.51825$	$\nu_{e35} = 63.93$	
	$r_{36} = \infty$			
	$d_{36} = 0.500$			

$$r_{37} = \infty \text{ (imaging surface)}$$

$$d_{37} = 0.000$$

Zoom data

		0.3×	0.4×	0.5×
5	D1	38.765	44.451	53.283
	D7	117.344	81.410	52.958
	D15	3.000	34.932	56.369
	D21	2.614	3.787	5.228
	D33	21.660	18.803	15.544
10	Parameters of conditions			
	Magnification : β	0.3×	0.4×	0.5×
	Entrance pupil position : E_n	1117.828	5171.585	-1158.986
	Object-to-image distance : L	432.125	432.125	432.125
	$ E_n / L$	2.587	11.968	2.682
15	Exit pupil position : E_x	-357.630	-357.630	-357.630
	$ E_x / L / \beta $	0.248	0.331	0.485
	F-number : FNO	3.500	3.479	3.414
	FNO fluctuation : ΔFNO	-0.046		
	$ \Delta FNO / \Delta \beta $	-0.228		
20	Object-side radius of curvature : R_{3f}	40.130		
	Image-side radius of curvature : R_{3b}	16.080		
	$ (R_{3f} + R_{3b}) / (R_{3f} - R_{3b}) $	2.337		

Fifth embodiment

25 Figs. 9A, 9B, and 9C show optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of the fifth embodiment of the imaging optical system according to the present invention. Figs. 10A, 10B, and 10C show aberration characteristics in focusing at a magnification of 0.4× of the imaging optical system in the fifth embodiment.

The imaging optical system of the fifth embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, a plano-convex lens L1₁' with a convex surface directed toward the object side and a plane surface directed toward the image side, the negative meniscus lens L1₂' with a convex surface directed toward the object side, and the positive meniscus lens L1₃' with a convex surface directed toward the object side.

The second lens unit G2, in order from the object side, the negative meniscus lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂, the negative meniscus lens L2₃ with a concave surface directed toward the object side, and the biconvex lens L2₄.

The third lens unit G3 includes the positive meniscus lens L3₁ with a convex surface directed toward the object side, the negative meniscus lens L3₂ with a convex surface directed toward the object side, and the negative meniscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes the cemented doublet of the biconcave lens L4₁ and the biconvex lens L4₂, the biconcave lens L4₃, the biconvex lens L4₄, the biconvex lens L4₅, and the biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1, after being moved once toward the object side, is moved toward the image side, the second lens unit G2 is moved toward the object side, the third lens unit G3 is moved toward the object side so that the spacing between the third and fourth lens units G3 and G4 is slightly widened, and the fourth

lens unit G4 remains fixed together with the stop S. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the fifth embodiment are shown below.

5 Numerical data 5

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

$$d_0 = 50.000$$

$$r_1 = \infty \text{ (object surface)}$$

10 $d_1 = D1$

$$r_2 = 53.6678$$

$$d_2 = 7.850 \quad n_{e2} = 1.48915 \quad v_{e2} = 70.04$$

$$r_3 = \infty$$

$$d_3 = 0.300$$

15 $r_4 = 74.4381$

$$d_4 = 6.000 \quad n_{e4} = 1.61639 \quad v_{e4} = 44.15$$

$$r_5 = 34.5362$$

$$d_5 = 8.043$$

$$r_6 = 39.1043$$

20 $d_6 = 4.857 \quad n_{e6} = 1.43985 \quad v_{e6} = 94.53$

$$r_7 = 52.1576$$

$$d_7 = D7$$

$$r_8 = 149.0540$$

$$d_8 = 6.000 \quad n_{e8} = 1.61639 \quad v_{e8} = 44.15$$

25 $r_9 = 50.6084$

$$d_9 = 6.908$$

$$r_{10} = 78.4447$$

$$d_{10} = 9.096 \quad n_{e10} = 1.43985 \quad v_{e10} = 94.53$$

	$r_{11} = -67.1214$			
	$d_{11} = 1.239$			
	$r_{12} = -55.5198$			
	$d_{12} = 7.000$	$n_{e12} = 1.61639$	$\nu_{e12} = 44.15$	
5	$r_{13} = -130.4767$			
	$d_{13} = 17.549$			
	$r_{14} = 526.4312$			
	$d_{14} = 10.495$	$n_{e14} = 1.43985$	$\nu_{e14} = 94.53$	
	$r_{15} = -60.7655$			
10	$d_{15} = D15$			
	$r_{16} = 42.8799$			
	$d_{16} = 4.607$	$n_{e16} = 1.69417$	$\nu_{e16} = 30.83$	
	$r_{17} = 241.5957$			
	$d_{17} = 0.300$			
15	$r_{18} = 24.0062$			
	$d_{18} = 9.266$	$n_{e18} = 1.72538$	$\nu_{e18} = 34.47$	
	$r_{19} = 20.0630$			
	$d_{19} = 1.423$			
	$r_{20} = 37.0493$			
20	$d_{20} = 2.000$	$n_{e20} = 1.72538$	$\nu_{e20} = 34.47$	
	$r_{21} = 16.8163$			
	$d_{21} = D21$			
	$r_{22} = \infty$ (aperture stop)			
	$d_{22} = 3.685$			
25	$r_{23} = -27.7248$			
	$d_{23} = 2.000$	$n_{e23} = 1.61669$	$\nu_{e23} = 44.02$	
	$r_{24} = 25.1231$			
	$d_{24} = 5.991$	$n_{e24} = 1.48915$	$\nu_{e24} = 70.04$	

	$r_{25} = -18.8837$			
	$d_{25} = 4.943$			
	$r_{26} = -14.1386$			
	$d_{26} = 0.553$	$n_{e26} = 1.61639$	$\nu_{e26} = 44.15$	
5	$r_{27} = 103.4372$			
	$d_{27} = 4.610$			
	$r_{28} = 946.2142$			
	$d_{28} = 8.426$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$	
	$r_{29} = -18.1453$			
10	$d_{29} = 0.300$			
	$r_{30} = 79.1515$			
	$d_{30} = 7.210$	$n_{e30} = 1.43985$	$\nu_{e30} = 94.53$	
	$r_{31} = -65.2376$			
	$d_{31} = 5.640$			
15	$r_{32} = 63.0290$			
	$d_{32} = 6.581$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$	
	$r_{33} = -291.4522$			
	$d_{33} = 19.405$			
	$r_{34} = \infty$			
20	$d_{34} = 33.000$	$n_{e34} = 1.61173$	$\nu_{e34} = 46.30$	
	$r_{35} = \infty$			
	$d_{35} = 13.200$	$n_{e35} = 1.51825$	$\nu_{e35} = 63.93$	
	$r_{36} = \infty$			
	$d_{36} = 0.500$			
25	$r_{37} = \infty$ (imaging surface)			
	$d_{37} = 0.000$			

Zoom data

0.3×

0.4×

0.5×

D1	42.960	38.372	47.817
D7	105.480	70.527	33.769
D15	3.000	40.551	66.211
D21	2.679	4.670	6.322

Parameters of conditions

Magnification : β	0.3×	0.4×	0.5×
Entrance pupil position : En	1295.110	24846.034	-1103.070
Object-to-image distance : L	423.096	423.096	423.096
$ En / L$	3.061	58.724	2.607
Exit pupil position : Ex	-366.274	-366.274	-366.274
$ Ex / L / \beta $	0.260	0.346	0.433
F-number : FNO	3.500	3.500	3.500
FNO fluctuation : ΔFNO	0.000		
$ \Delta FNO / \Delta \beta $	-0.002		
Object-side radius of curvature : R3f	42.880		
Image-side radius of curvature : R3b	16.816		
$ (R3f + R3b) / (R3f - R3b) $	2.290		

Sixth embodiment

Figs. 11A, 11B, and 11C show optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of the sixth embodiment of the imaging optical system according to the present invention. Figs. 12A, 12B, and 12C show aberration characteristics in focusing at a magnification of 0.4× of the imaging optical system in the sixth embodiment.

The imaging optical system of the sixth embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with nega-

tive refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, the biconvex lens L1₁, the biconcave lens L1₂, and the biconvex lens L1₃.

5 The second lens unit G2, in order from the object side, the negative meniscus lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂, the negative meniscus lens L2₃ with a concave surface directed toward the object side, and a positive meniscus lens L2₄' with a concave surface directed toward the object side.

10 The third lens unit G3 includes the positive meniscus lens L3₁ with a convex surface directed toward the object side, the negative meniscus lens L3₂ with a convex surface directed toward the object side, and the negative meniscus lens L3₃ with a convex surface directed toward the object side.

15 The fourth lens unit G4 includes the cemented doublet of the biconcave lens L4₁ and the biconvex lens L4₂, the biconcave lens L4₃, the biconvex lens L4₄, the biconvex lens L4₅, and the biconvex lens L4₆.

20 When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1 is moved toward the object side, the second lens unit G2 is moved toward the object side so that spacing between the first and second lens units G1 and G2 is widened, the third lens unit G3 is moved together with the stop S toward the image side, and the fourth lens unit G4 is moved toward the image side so that the spacing between the third and fourth lens units G3 and G4 is slightly widened. Also, the object-to-image distance in the magnification change is kept constant.

25 Subsequently, numerical data of optical members constituting the imaging optical system of the sixth embodiment are shown below.

Numerical data 6

Image height : 5.783

	$r_0 = \infty$ (object)			
	$d_0 = 50.000$			
	$r_1 = \infty$ (object surface)			
	$d_1 = D1$			
5	$r_2 = 361.3250$			
	$d_2 = 12.000$	$n_{e2} = 1.48915$	$\nu_{e2} = 70.04$	
	$r_3 = -65.3190$			
	$d_3 = 0.300$			
	$r_4 = -90.3503$			
10	$d_4 = 8.000$	$n_{e4} = 1.61639$	$\nu_{e4} = 44.15$	
	$r_5 = 45.5593$			
	$d_5 = 11.355$			
	$r_6 = 65.7955$			
	$d_6 = 12.000$	$n_{e6} = 1.43985$	$\nu_{e6} = 94.53$	
15	$r_7 = -101.4028$			
	$d_7 = D7$			
	$r_8 = 113.0032$			
	$d_8 = 7.000$	$n_{e8} = 1.61639$	$\nu_{e8} = 44.15$	
	$r_9 = 53.1618$			
20	$d_9 = 7.854$			
	$r_{10} = 84.6315$			
	$d_{10} = 8.348$	$n_{e10} = 1.43985$	$\nu_{e10} = 94.53$	
	$r_{11} = -82.9242$			
	$d_{11} = 2.346$			
25	$r_{12} = -51.6817$			
	$d_{12} = 6.901$	$n_{e12} = 1.61639$	$\nu_{e12} = 44.15$	
	$r_{13} = -78.9538$			
	$d_{13} = 0.300$			

	$r_{14} = -746.1406$			
	$d_{14} = 7.363$	$n_{e14} = 1.43985$	$v_{e14} = 94.53$	
	$r_{15} = -54.9986$			
	$d_{15} = D15$			
5	$r_{16} = 40.2152$			
	$d_{16} = 4.672$	$n_{e16} = 1.69417$	$v_{e16} = 30.83$	
	$r_{17} = 202.9669$			
	$d_{17} = 0.300$			
	$r_{18} = 25.2156$			
10	$d_{18} = 9.337$	$n_{e18} = 1.72538$	$v_{e18} = 34.47$	
	$r_{19} = 20.5989$			
	$d_{19} = 1.486$			
	$r_{20} = 47.2290$			
	$d_{20} = 2.000$	$n_{e20} = 1.72538$	$v_{e20} = 34.47$	
15	$r_{21} = 17.1952$			
	$d_{21} = D21$			
	$r_{22} = \infty$ (aperture stop)			
	$d_{22} = 8.090$			
	$r_{23} = -31.8155$			
20	$d_{23} = 12.000$	$n_{e23} = 1.61669$	$v_{e23} = 44.02$	
	$r_{24} = 23.4115$			
	$d_{24} = 6.316$	$n_{e24} = 1.48915$	$v_{e24} = 70.04$	
	$r_{25} = -23.1015$			
	$d_{25} = 1.525$			
25	$r_{26} = -17.3296$			
	$d_{26} = 0.137$	$n_{e26} = 1.61639$	$v_{e26} = 44.15$	
	$r_{27} = 121.5936$			
	$d_{27} = 4.365$			

	$r_{28} = 236.9154$			
	$d_{28} = 8.477$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$	
	$r_{29} = -20.8758$			
	$d_{29} = 0.300$			
5	$r_{30} = 78.3373$			
	$d_{30} = 5.274$	$n_{e30} = 1.43985$	$\nu_{e30} = 94.53$	
	$r_{31} = -103.6059$			
	$d_{31} = 0.983$			
	$r_{32} = 81.5041$			
10	$d_{32} = 5.879$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$	
	$r_{33} = -103.9512$			
	$d_{33} = D33$			
	$r_{34} = \infty$			
	$d_{34} = 33.000$	$n_{e34} = 1.61173$	$\nu_{e34} = 46.30$	
15	$r_{35} = \infty$			
	$d_{35} = 13.200$	$n_{e35} = 1.51825$	$\nu_{e35} = 63.93$	
	$r_{36} = \infty$			
	$d_{36} = 0.500$			
	$r_{37} = \infty$ (imaging surface)			
20	$d_{37} = 0.000$			

Zoom data

		0.3×	0.4×	0.5×
	D1	68.668	51.352	36.703
	D7	65.281	56.350	50.311
25	D15	3.000	32.024	53.396
	D21	2.770	2.825	3.398
	D33	20.686	17.854	16.597

Parameters of conditions

	Magnification : β	0.3×	0.4×	0.5×
	Entrance pupil position : En	140.733	198.229	329.610
	Object-to-image distance : L	412.012	412.012	412.012
	En / L	0.342	0.481	0.800
5	Exit pupil position : Ex	2022.944	2022.944	2022.944
	Ex / L / β	1.473	1.964	2.455
	F-number : FNO	3.500	3.511	3.516
	FNO fluctuation : Δ FNO	0.016		
	Δ FNO / $\Delta\beta$	0.082		
10	Object-side radius of curvature : R3f	40.215		
	Image-side radius of curvature : R3b	17.195		
	(R3f + R3b) / (R3f – R3b)	2.494		

Seventh embodiment

15 Figs. 13A, 13B, and 13C show optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of the seventh embodiment of the imaging optical system according to the present invention. Figs. 14A, 14B, and 14C show aberration characteristics in focusing at a magnification of 0.4× of the imaging optical system in the seventh embodiment.

20 The imaging optical system of the seventh embodiment has the variable magnification optical system Z. In Fig. 13A, reference symbol GL designates a plane-parallel plate and P1 and P2 designate prisms.

25 The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, the biconvex lens L1₁, the negative meniscus lens L1₂' with a convex surface directed toward the object

side, and the positive meniscus lens L1₃' with a convex surface directed toward the object side.

The second lens unit G2, in order from the object side, the negative meniscus lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂,
5 the negative meniscus lens L2₃ with a concave surface directed toward the object side, and the biconvex lens L2₄.

The third lens unit G3 includes the positive meniscus lens L3₁ with a convex surface directed toward the object side, the negative meniscus lens L3₂ with a convex surface directed toward the object side, and the negative meniscus lens L3₃ with a
10 convex surface directed toward the object side.

The fourth lens unit G4 includes the cemented doublet of the biconcave lens L4₁ and the biconvex lens L4₂, the biconcave lens L4₃, a positive meniscus lens L4₄' with a concave surface directed toward the object side, the biconvex lens L4₅, and the biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1 is moved toward the object side, the second lens unit G2 is moved toward the object side so that the spacing between the first and second lens units G1 and G2 is narrowed, the third lens unit G3 is moved together with the stop S toward the image side, and the fourth lens unit G4 is moved toward
20 the image side so that the spacing between the third and fourth lens units G3 and G4 is slightly widened. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the seventh embodiment are shown below.

Numerical data 7

Image height : 5.783

$$r_o = \infty \text{ (object)}$$

$$d_o = 51.000$$

	$r_1 = \infty$ (object surface)			
	$d_1 = 9.260$	$n_{e1} = 1.51825$	$v_{e1} = 63.93$	
	$r_2 = \infty$			
	$d_2 = 2.740$			
5	$r_3 = \infty$			
	$d_3 = 35.000$			
	$r_4 = \infty$			
	$d_4 = 60.000$	$n_{e4} = 1.51825$	$v_{e4} = 63.93$	
	$r_5 = \infty$			
10	$d_5 = D5$			
	$r_6 = 206.3131$			
	$d_6 = 6.508$	$n_{e6} = 1.48915$	$v_{e6} = 70.04$	
	$r_7 = -156.0897$			
	$d_7 = 15.114$			
15	$r_8 = 130.1657$			
	$d_8 = 8.000$	$n_{e8} = 1.61639$	$v_{e8} = 44.15$	
	$r_9 = 61.3830$			
	$d_9 = 1.693$			
	$r_{10} = 80.8720$			
20	$d_{10} = 12.000$	$n_{e10} = 1.43985$	$v_{e10} = 94.53$	
	$r_{11} = 232.8980$			
	$d_{11} = D11$			
	$r_{12} = 672.7620$			
	$d_{12} = 6.836$	$n_{e12} = 1.61639$	$v_{e12} = 44.15$	
25	$r_{13} = 82.8549$			
	$d_{13} = 2.818$			
	$r_{14} = 110.5678$			
	$d_{14} = 9.282$	$n_{e14} = 1.43985$	$v_{e14} = 94.53$	

	$r_{15} = -65.4332$			
	$d_{15} = 0.300$			
	$r_{16} = -67.0268$			
	$d_{16} = 6.107$	$n_{e16} = 1.61639$	$\nu_{e16} = 44.15$	
5	$r_{17} = -156.9702$			
	$d_{17} = 50.171$			
	$r_{18} = 160.2358$			
	$d_{18} = 10.874$	$n_{e18} = 1.43985$	$\nu_{e18} = 94.53$	
	$r_{19} = -98.7058$			
10	$d_{19} = D19$			
	$r_{20} = 37.4259$			
	$d_{20} = 5.034$	$n_{e20} = 1.69417$	$\nu_{e20} = 30.83$	
	$r_{21} = 212.9113$			
	$d_{21} = 0.300$			
15	$r_{22} = 22.9775$			
	$d_{22} = 8.363$	$n_{e22} = 1.72538$	$\nu_{e22} = 34.47$	
	$r_{23} = 18.2286$			
	$d_{23} = 1.827$			
	$r_{24} = 101.2051$			
20	$d_{24} = 2.247$	$n_{e24} = 1.72538$	$\nu_{e24} = 34.47$	
	$r_{25} = 17.6992$			
	$d_{25} = 2.554$			
	$r_{26} = \infty$ (aperture stop)			
	$d_{26} = D26$			
25	$r_{27} = -55.3149$			
	$d_{27} = 2.589$	$n_{e27} = 1.61669$	$\nu_{e27} = 44.02$	
	$r_{28} = 20.3875$			
	$d_{28} = 11.136$	$n_{e28} = 1.48915$	$\nu_{e28} = 70.04$	

	$r_{29} = -22.7793$			
	$d_{29} = 2.967$			
	$r_{30} = -17.4070$			
	$d_{30} = 2.255$	$n_{e30} = 1.61639$	$\nu_{e30} = 44.15$	
5	$r_{31} = 660.0000$			
	$d_{31} = 5.164$			
	$r_{32} = -361.4116$			
	$d_{32} = 9.280$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$	
	$r_{33} = -21.6618$			
10	$d_{33} = 0.300$			
	$r_{34} = 57.4166$			
	$d_{34} = 5.104$	$n_{e34} = 1.43985$	$\nu_{e34} = 94.53$	
	$r_{35} = -177.5066$			
	$d_{35} = 0.350$			
15	$r_{36} = 61.7155$			
	$d_{36} = 4.849$	$n_{e36} = 1.43985$	$\nu_{e36} = 94.53$	
	$r_{37} = -672.7620$			
	$d_{37} = D37$			
	$r_{38} = \infty$			
20	$d_{38} = 33.000$	$n_{e38} = 1.61173$	$\nu_{e38} = 46.30$	
	$r_{39} = \infty$			
	$d_{39} = 13.200$	$n_{e39} = 1.51825$	$\nu_{e39} = 63.93$	
	$r_{40} = \infty$			
	$d_{40} = 0.500$			
25	$r_{41} = \infty$ (imaging surface)			
	$d_{41} = 0.000$			

Zoom data

0.3×

0.4×

0.5×

	D5	32.142	28.009	24.962
	D11	58.194	27.683	8.473
	D19	3.000	39.963	64.634
	D26	3.340	5.440	7.048
5	D37	23.777	19.357	15.336
Parameters of conditions				
	Magnification : β	0.3×	0.4×	0.5×
	Entrance pupil position : En	1215.330	17052.978	-1195.682
	Object-to-image distance : L	467.675	467.675	467.675
10	En / L	2.599	36.463	2.557
	Exit pupil position : Ex	-361.027	-890.944	-13016.681
	Ex / L / β	0.232	0.762	13.916
	F-number : FNO	3.500	3.517	3.556
	FNO fluctuation : Δ FNO	0.056		
15	Δ FNO / $\Delta\beta$	0.280		
	Object-side radius of curvature : R3f	37.426		
	Image-side radius of curvature : R3b	17.699		
	(R3f + R3b) / (R3f – R3b)	2.794		

Eighth embodiment

20 Figs. 15A, 15B, and 15C show optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of the eighth embodiment of the imaging optical system according to the present invention. Figs. 16A, 16B, and 16C show aberration characteristics in focusing at a magnification of 0.4× of the imaging optical system in the eighth embodiment.

25 The imaging optical system of the eighth embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the

second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, a positive meniscus lens L1₁" with a concave surface directed toward the object side, the negative meniscus lens L1₂' with a concave surface directed toward the object side, and the biconvex lens L1₃.

The second lens unit G2, in order from the object side, the negative meniscus lens L2₁ with a convex surface directed toward the object side, the biconvex lens L2₂, the negative meniscus lens L2₃ with a concave surface directed toward the object side, the positive meniscus lens L2₄' with a concave surface directed toward the object side, and a positive meniscus lens L2₅ with a convex surface directed toward the object side.

The third lens unit G3 includes a biconvex lens L3₁', the negative meniscus lens L3₂ with a convex surface directed toward the object side, and the negative meniscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes a negative meniscus lens L4₁' with a convex surface directed toward the object side, a positive meniscus lens L4₂' with a concave surface directed toward the object side, a negative meniscus lens L4₃' with a concave surface directed toward the object side, the positive meniscus lens L4₄' with a concave surface directed toward the object side, the biconvex lens L4₅, and a positive meniscus lens L4₆' with a convex surface directed toward the object side.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1 is moved toward the object side, the second lens unit G2 is moved toward the object side so that the spacing between the first and second lens units G1 and G2 is widened, the third lens unit G3 is moved together with the stop S toward the object side so that the spacing between the second and third lens units G2 and G3 is slightly widened, and the fourth lens unit G4, after be-

ing slightly moved once toward the image side, is slightly moved toward the object side. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the eighth embodiment are shown below.

Numerical data 8

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

$$d_0 = 51.000$$

$$r_1 = \infty \text{ (object surface)}$$

$$d_1 = 9.260 \quad n_{e1} = 1.51825 \quad v_{e1} = 63.93$$

$$r_2 = \infty$$

$$d_2 = 2.740$$

$$r_3 = \infty$$

$$d_3 = 35.000$$

$$r_4 = \infty$$

$$d_4 = 60.000 \quad n_{e4} = 1.51825 \quad v_{e4} = 63.93$$

$$r_5 = \infty$$

$$d_5 = D5$$

$$r_6 = -218.393$$

$$d_6 = 11.966 \quad n_{e6} = 1.48915 \quad v_{e6} = 70.04$$

$$r_7 = -59.981$$

$$d_7 = 0.724$$

$$r_8 = -58.074$$

$$d_8 = 8.000 \quad n_{e8} = 1.61639 \quad v_{e8} = 44.15$$

$$r_9 = -192.015$$

$$d_9 = 0.300$$

$$r_{10} = 453.258$$

	$d_{10} = 11.399$	$n_{e10} = 1.43985$	$\nu_{e10} = 94.53$
	$r_{11} = -95.008$		
	$d_{11} = D11$		
	$r_{12} = 111.240$		
5	$d_{12} = 6.982$	$n_{e12} = 1.61639$	$\nu_{e12} = 44.15$
	$r_{13} = 49.021$		
	$d_{13} = 0.808$		
	$r_{14} = 52.125$		
	$d_{14} = 6.307$	$n_{e14} = 1.43985$	$\nu_{e14} = 94.53$
10	$r_{15} = -602.409$		
	$d_{15} = 3.345$		
	$r_{16} = -51.702$		
	$d_{16} = 7.000$	$n_{e16} = 1.61639$	$\nu_{e16} = 44.15$
	$r_{17} = -123.131$		
15	$d_{17} = 0.300$		
	$r_{18} = -267.367$		
	$d_{18} = 5.244$	$n_{e18} = 1.43985$	$\nu_{e18} = 94.53$
	$r_{19} = -59.230$		
	$d_{19} = 0.300$		
20	$r_{20} = 62.890$		
	$d_{20} = 5.562$	$n_{e20} = 1.43985$	$\nu_{e20} = 94.53$
	$r_{21} = 208.855$		
	$d_{21} = D21$		
	$r_{22} = 109.670$		
25	$d_{22} = 4.560$	$n_{e22} = 1.67765$	$\nu_{e22} = 31.84$
	$r_{23} = -261.555$		
	$d_{23} = 4.236$		
	$r_{24} = 27.656$		

	$d_{24} = 9.660$	$n_{e24} = 1.83945$	$\nu_{e24} = 42.47$
	$r_{25} = 22.416$		
	$d_{25} = 3.719$		
	$r_{26} = 591.785$		
5	$d_{26} = 2.000$	$n_{e26} = 1.83945$	$\nu_{e26} = 42.47$
	$r_{27} = 32.027$		
	$d_{27} = 2.504$		
	$r_{28} = \infty$ (aperture stop)		
	$d_{28} = D28$		
10	$r_{29} = 235.972$		
	$d_{29} = 3.058$	$n_{e29} = 1.61639$	$\nu_{e29} = 44.15$
	$r_{30} = 39.062$		
	$d_{30} = 3.236$		
	$r_{31} = -23.495$		
15	$d_{31} = 6.117$	$n_{e31} = 1.43985$	$\nu_{e31} = 94.53$
	$r_{32} = -17.821$		
	$d_{32} = 0.300$		
	$r_{33} = -18.080$		
	$d_{33} = 4.802$	$n_{e33} = 1.61639$	$\nu_{e33} = 44.15$
20	$r_{34} = -31.126$		
	$d_{34} = 0.300$		
	$r_{35} = -67.557$		
	$d_{35} = 4.329$	$n_{e35} = 1.43985$	$\nu_{e35} = 94.53$
	$r_{36} = -32.513$		
25	$d_{36} = 0.300$		
	$r_{37} = 81.623$		
	$d_{37} = 4.159$	$n_{e37} = 1.43985$	$\nu_{e37} = 94.53$
	$r_{38} = -357.038$		

	$d_{38} = 0.484$		
	$r_{39} = 34.763$		
	$d_{39} = 5.000$	$n_{e39} = 1.43985$	$\nu_{e39} = 94.53$
	$r_{40} = 244.020$		
5	$d_{40} = D40$		
	$r_{41} = \infty$		
	$d_{41} = 33.000$	$n_{e41} = 1.61173$	$\nu_{e41} = 46.30$
	$r_{42} = \infty$		
	$d_{42} = 13.200$	$n_{e42} = 1.51825$	$\nu_{e42} = 63.93$
10	$r_{43} = \infty$		
	$d_{43} = 0.500$		
	$r_{44} = \infty$ (imaging surface)		
	$d_{44} = 0$		

Zoom data

15		0.3×	0.4×	0.5×
	D5	193.324	142.895	90.403
	D11	3.000	43.660	80.930
	D21	3.160	6.077	8.978
	D28	20.516	27.628	34.649
20	D40	11.289	11.032	16.330

Parameters of conditions

	Magnification : β	0.3×	0.4×	0.5×
	Entrance pupil position : En	89.768	209.179	450.391
	Object-to-image distance : L	562.991	562.991	562.991
25	$ En / L$	0.159	0.372	0.800
	Exit pupil position : Ex	-355.985	-5834.634	634.502
	$ Ex / L / \beta $	0.190	4.145	0.564
	F-number : FNO	3.500	3.789	4.037

FNO fluctuation : ΔFNO	0.537
$ \Delta FNO / \Delta \beta $	2.685
Object-side radius of curvature : $R3f$	109.670
Image-side radius of curvature : $R3b$	32.027
$ (R3f + R3b) / (R3f - R3b) $	1.825

Ninth embodiment

Figs. 17A, 17B, and 17C show optical arrangements, developed along the optical axis, at magnifications of 0.3×, 0.4×, and 0.5×, respectively, of the ninth embodiment of the imaging optical system according to the present invention. Figs. 18A, 18B, and 18C show aberration characteristics in focusing at a magnification of 0.4× of the imaging optical system in the ninth embodiment.

The imaging optical system of the ninth embodiment has the variable magnification optical system Z.

The variable magnification optical system Z comprises, in order from the object side toward the image side, the first lens unit G1 with positive refractive power, the second lens unit G2 with positive refractive power, the third lens unit G3 with negative refractive power, the aperture stop S, and the fourth lens unit G4 with positive refractive power.

The first lens unit G1 includes, in order from the object side, the positive meniscus lens $L1_1$ with a concave surface directed toward the object side, the negative meniscus lens $L1_2$ with a concave surface directed toward the object side, and a positive meniscus lens $L1_3$ with a concave surface directed toward the object side.

The second lens unit G2, in order from the object side, the negative meniscus lens $L2_1$ with a convex surface directed toward the object side, the biconvex lens $L2_2$, the negative meniscus lens $L2_3$ with a concave surface directed toward the object side, the biconvex lens $L2_4$, and a biconvex lens $L2_5$.

The third lens unit G3 includes the biconvex lens $L3_1$, the negative meniscus lens $L3_2$ with a convex surface directed toward the object side, and the negative me-

niscus lens L3₃ with a convex surface directed toward the object side.

The fourth lens unit G4 includes a negative meniscus lens L4₁" with a concave surface directed toward the object side, the positive meniscus lens L4₂' with a concave surface directed toward the object side, the negative meniscus lens L4₃' with a concave surface directed toward the object side, the positive meniscus lens L4₄' with a concave surface directed toward the object side, the biconvex lens L4₅, and the biconvex lens L4₆.

When the magnification is changed from 0.3× to 0.5× in focusing of the infinite object point, the first lens unit G1 is moved toward the object side, the second lens unit G2 is moved toward the object side so that the spacing between the first and second lens units G1 and G2 is widened, the third lens unit G3 is moved together with the stop S toward the object side so that the spacing between the second and third lens units G2 and G3 is widened, and the fourth lens unit G4, after being slightly moved once toward the image side, is slightly moved toward the object side. Also, the object-to-image distance in the magnification change is kept constant.

Subsequently, numerical data of optical members constituting the imaging optical system of the ninth embodiment are shown below.

Numerical data 9

Image height : 5.783

$$r_0 = \infty \text{ (object)}$$

$$d_0 = 21.000$$

$$r_1 = \infty \text{ (object)}$$

$$d_1 = 26.161$$

$$r_2 = \infty \text{ (object surface)}$$

$$d_2 = D2$$

$$r_3 = -153.3010$$

$$d_3 = 12.000$$

$$n_{e3} = 1.48915$$

$$\nu_{e3} = 70.04$$

$$r_4 = -56.0044$$

	$d_4 = 6.782$		
	$r_5 = -42.5771$		
	$d_5 = 8.000$	$n_{e5} = 1.61639$	$v_{e5} = 44.15$
	$r_6 = -173.4981$		
5	$d_6 = 15.255$		
	$r_7 = -454.5776$		
	$d_7 = 12.000$	$n_{e7} = 1.43985$	$v_{e7} = 94.53$
	$r_8 = -54.2450$		
	$d_8 = D8$		
10	$r_9 = 74.1238$		
	$d_9 = 7.000$	$n_{e9} = 1.61639$	$v_{e9} = 44.15$
	$r_{10} = 47.9620$		
	$d_{10} = 0.782$		
	$r_{11} = 50.6461$		
15	$d_{11} = 6.639$	$n_{e11} = 1.43985$	$v_{e11} = 94.53$
	$r_{12} = -395.4325$		
	$d_{12} = 2.526$		
	$r_{13} = -67.4730$		
	$d_{13} = 6.000$	$n_{e13} = 1.61639$	$v_{e13} = 44.15$
20	$r_{14} = -489.0704$		
	$d_{14} = 0.300$		
	$r_{15} = 162.7339$		
	$d_{15} = 5.252$	$n_{e15} = 1.43985$	$v_{e15} = 94.53$
	$r_{16} = -122.6735$		
25	$d_{16} = 0.300$		
	$r_{17} = 377.7299$		
	$d_{17} = 4.142$	$n_{e17} = 1.43985$	$v_{e17} = 94.53$
	$r_{18} = -202.1041$		

	$d_{18} = D18$		
	$r_{19} = 108.3047$		
	$d_{19} = 4.106$	$n_{e19} = 1.67765$	$\nu_{e19} = 31.84$
	$r_{20} = -192.0405$		
5	$d_{20} = 0.454$		
	$r_{21} = 25.9085$		
	$d_{21} = 9.623$	$n_{e21} = 1.83945$	$\nu_{e21} = 42.47$
	$r_{22} = 24.8614$		
	$d_{22} = 2.939$		
10	$r_{23} = 50.8391$		
	$d_{23} = 2.000$	$n_{e23} = 1.83945$	$\nu_{e23} = 42.47$
	$r_{24} = 18.5107$		
	$d_{24} = 3.223$		
	$r_{25} = \infty$ (aperture stop)		
15	$d_{25} = D25$		
	$r_{26} = -23.8975$		
	$d_{26} = 8.198$	$n_{e26} = 1.61639$	$\nu_{e26} = 44.15$
	$r_{27} = -142.2318$		
	$d_{27} = 1.569$		
20	$r_{28} = -27.6769$		
	$d_{28} = 12.000$	$n_{e28} = 1.43985$	$\nu_{e28} = 94.53$
	$r_{29} = -15.4629$		
	$d_{29} = 0.617$		
	$r_{30} = -15.4255$		
25	$d_{30} = 2.000$	$n_{e30} = 1.61639$	$\nu_{e30} = 44.15$
	$r_{31} = -31.9175$		
	$d_{31} = 0.300$		
	$r_{32} = -193.4359$		

	$d_{32} = 5.561$	$n_{e32} = 1.43985$	$\nu_{e32} = 94.53$
	$r_{33} = -30.6965$		
	$d_{33} = 0.300$		
	$r_{34} = 190.3831$		
5	$d_{34} = 4.818$	$n_{e34} = 1.43985$	$\nu_{e34} = 94.53$
	$r_{35} = -61.6979$		
	$d_{35} = 0.300$		
	$r_{36} = 63.1906$		
	$d_{36} = 4.652$	$n_{e36} = 1.43985$	$\nu_{e36} = 94.53$
10	$r_{37} = -264.7349$		
	$d_{37} = D37$		
	$r_{38} = \infty$		
	$d_{38} = 33.000$	$n_{e38} = 1.61173$	$\nu_{e38} = 46.30$
	$r_{39} = \infty$		
15	$d_{39} = 13.200$	$n_{e39} = 1.51825$	$\nu_{e39} = 63.93$
	$r_{40} = \infty$		
	$d_{40} = 0.500$		
	$r_{41} = \infty$ (imaging surface)		
	$d_{41} = 0.000$		

20 Zoom data

	0.3×	0.4×	0.5×
D2	131.948	109.433	66.283
D8	3.000	7.576	32.565
D18	3.338	20.375	31.678
25 D25	6.470	11.057	13.774
D37	16.892	13.207	17.349

Parameters of conditions

Magnification : β	0.3×	0.4×	0.5×
-------------------------	------	------	------

	Entrance pupil position : E_n	104.859	165.265	302.380
	Object-to-image distance : L	405.147	405.147	405.147
	$ E_n / L$	0.259	0.408	0.746
	Exit pupil position : E_x	-368.020	2564.601	598.424
5	$ E_x / L / \beta $	0.273	2.532	0.739
	F-number : FNO	3.500	3.725	3.839
	FNO fluctuation : ΔFNO	0.339		
	$ \Delta FNO / \Delta \beta $	1.693		
	Object-side radius of curvature : R_{3f}	108.305		
10	Image-side radius of curvature : R_{3b}	18.511		
	$ (R_{3f} + R_{3b}) / (R_{3f} - R_{3b}) $	1.412		

Subsequently, parameter values of the conditions in the above embodiments and whether the arrangements of the embodiments satisfy the requirements of the present invention are summarized in Tables 1 through 3.

Table 1

	First embodiment	Second embodiment	Third embodiment
Object-side telecentricity E_n / L ($\beta = 0.3$)	2.71	2.62	2.96
Object-side telecentricity E_n / L ($\beta = 0.4$)	47.27	38.41	42.84
Object-side telecentricity E_n / L ($\beta = 0.5$)	2.65	2.66	2.55
Image-side telecentricity E_n / L / β ($\beta = 0.3$)	0.25	0.25	0.25
Image-side telecentricity E_n / L / β ($\beta = 0.4$)	0.54	0.69	0.84
Image-side telecentricity E_n / L / β ($\beta = 0.5$)	2.12	28.49	5.62
Conditions (1), (2)	O	O	O
Conditions (1'), (2')	O	O	O
Conditions (1''), (2'')	O	O	O
Difference between object-to-image distances at 0.3× and 0.5×	0.00000	0.00002	0.00000
Smallest object-side F-number, MAXFNO	3.5	3.5	3.5
$\Delta FNO / \Delta \beta$	0.49	0.729	0.935
Conditions (3), (4)	O	O	O
Conditions (3'), (4')	O	O	O
Conditions (3''), (4'')	O	O	O
Lens arrangement of 1st lens unit; positive	O	O	O
Lens arrangement of 1st lens unit; positive, negative	O	O	O
Lens arrangement of 1st lens unit; positive, negative, positive	O	O	O
Virtual shape factor of 3rd lens unit $(R3f + R3b) / (R3f - R3b)$	2.27	2.69	2.32
Condition (5)	O	O	O
Condition (5')	O	O	O
Condition (5'')	O	O	O
3rd lens unit : at least two meniscus lenses, each with a convex surface directed toward the object side	O	O	O
3rd lens unit : at least three meniscus lenses, each with a convex surface directed toward the object side	O	O	O

Note: O indicates that the condition is satisfied and × indicates that the condition is not satisfied.

Table 2

	Fourth embodiment	Fifth embodiment	Sixth embodiment
Object-side telecentricity $ E_n /L$ ($\beta = 0.3$)	2.59	3.06	0.34
Object-side telecentricity $ E_n /L$ ($\beta = 0.4$)	11.97	58.72	0.48
Object-side telecentricity $ E_n /L$ ($\beta = 0.5$)	2.68	2.61	0.80
Image-side telecentricity $ E_n / L/\beta $ ($\beta = 0.3$)	0.25	0.26	1.47
Image-side telecentricity $ E_n / L/\beta $ ($\beta = 0.4$)	0.33	0.35	1.96
Image-side telecentricity $ E_n / L/\beta $ ($\beta = 0.5$)	0.41	0.43	2.46
Conditions (1), (2)	O	O	O
Conditions (1'), (2')	×	×	O
Conditions (1''), (2'')	×	×	×
Difference between object-to-image distances at 0.3× and 0.5×	0.00000	0.00000	0.00000
Smallest object-side F-number, MAXFNO	3.45	3.5	3.5
$ \Delta FNO / \Delta \beta $	0.228	0.002	0.082
Conditions (3), (4)	O	O	O
Conditions (3'), (4')	O	O	O
Conditions (3''), (4'')	O	O	O
Lens arrangement of 1st lens unit; positive	O	O	O
Lens arrangement of 1st lens unit; positive, negative	O	O	O
Lens arrangement of 1st lens unit; positive, negative, positive	O	O	O
Virtual shape factor of 3rd lens unit $ (R3f + R3b) / (R3f - R3b) $	2.34	2.29	2.494
Condition (5)	O	O	O
Condition (5')	O	O	O
Condition (5'')	O	O	O
3rd lens unit : at least two meniscus lenses, each with a convex surface directed toward the object side	O	O	O
3rd lens unit : at least three meniscus lenses, each with a convex surface directed toward the object side	O	O	O

Note: O indicates that the condition is satisfied and × indicates that the condition is not satisfied.

Table 3

	Seventh embodiment	Eighth embodiment	Ninth embodiment
Object-side telecentricity E_n / L ($\beta = 0.3$)	2.60	0.16	0.26
Object-side telecentricity E_n / L ($\beta = 0.4$)	36.46	0.37	0.41
Object-side telecentricity E_n / L ($\beta = 0.5$)	2.56	0.80	0.75
Image-side telecentricity E_n / L / β ($\beta = 0.3$)	0.23	0.19	0.27
Image-side telecentricity E_n / L / β ($\beta = 0.4$)	0.76	4.15	2.53
Image-side telecentricity E_n / L / β ($\beta = 0.5$)	13.92	0.56	0.74
Conditions (1), (2)	O	O	O
Conditions (1'), (2')	O	×	×
Conditions (1''), (2'')	O	×	×
Difference between object-to-image distances at 0.3× and 0.5×	0.00000	0.00000	0.00000
Smallest object-side F-number, MAXFNO	3.51	3.5	3.5
ΔFNO / $\Delta \beta$	0.304	2.685	1.693
Conditions (3), (4)	O	O	O
Conditions (3'), (4')	O	O	O
Conditions (3''), (4'')	O	×	×
Lens arrangement of 1st lens unit; positive	O	O	O
Lens arrangement of 1st lens unit; positive, negative	O	O	O
Lens arrangement of 1st lens unit; positive, negative, positive	O	O	O
Virtual shape factor of 3rd lens unit $(R3f + R3b) / (R3f - R3b)$	2.69	1.83	1.41
Condition (5)	O	O	O
Condition (5')	O	O	O
Condition (5'')	O	×	×
3rd lens unit : at least two meniscus lenses, each with a convex surface directed toward the object side	O	O	O
3rd lens unit : at least three meniscus lenses, each with a convex surface directed toward the object side	O	×	×

Note: O indicates that the condition is satisfied and × indicates that the condition is not satisfied.

The imaging optical system of the present invention described above can be used in an optical apparatus such as a motion picture film scanner (a telecine apparatus) or a height measuring apparatus. Embodiments of such apparatuses are described below.

5 Fig. 19 shows an embodiment of the telecine apparatus using the imaging optical system of the present invention. This telecine apparatus includes a light source 11 for projecting a motion picture, a motion picture film 14 wound on reels 12 and 13, an imaging optical system 15, such as that disclosed by each embodiment in the present invention, and a CCD camera 16. In the figure, the specific arrangement of
10 the imaging optical system 15 is omitted.

In the telecine apparatus of this embodiment constructed as mentioned above, light emitted from the light source 11 is projected on the motion picture film 14, and projected light is imaged by the CCD camera 16 through the imaging optical system 15. In the imaging optical system 15, the magnification can be changed so that the
15 image information of the motion picture film 14 is imaged over the entire imaging area of the CCD camera 16 in accordance with the size of the motion picture film 14.

According to the telecine apparatus of the embodiment, the imaging optical system 15 is both-side telecentric so that even when the imaging magnification is changed, the conjugate length remains unchanged. Therefore, there is no need to
20 adjust the positions of individual members. Since the fluctuation of the image-side F-number is minimized and a loss of the amount of light is reduced, the adjustment of brightness is unnecessary. Moreover, a change in magnification on an image plane, caused by the disturbance of flatness of an object to be photographed, such as the film, can be kept to a minimum.

25 Fig. 20 shows an embodiment of the height measuring apparatus using the imaging optical system of the present invention. In this embodiment, the imaging optical system is used as a confocal optical system.

The height measuring apparatus of the embodiment includes a light source 21, a

polarization beam splitter 22, a disk 23 provided with a plurality of pinholes, a quarter-wave plate 24, a confocal optical system 25 constructed like the imaging optical system disclosed by each embodiment in the present invention, an XYZ stage 26, an imaging lens 27, an image sensor 28, a motor 29 driving the disk 23, a stage driving mechanism 30 driving the XYZ stage 26, a sensor driving mechanism 31 driving the image sensor 28, and a computer 32 controlling the drive of the motor 29, the stage driving mechanism 30, and the sensor driving mechanism 31.

In the height measuring apparatus of the embodiment constructed as mentioned above, a p or s component of linear polarization, of light emitted from the light source 21, is reflected by the polarization beam splitter 22, passes through the pinhole provided on the disk 23, and suffers a phase shift of 45° through the quarter-wave plate 24 to irradiate a certain point of a specimen 33 placed on the XYZ stage 26 through the confocal optical system 25. Light reflected by the specimen 33 passes through the confocal optical system 25, suffers a phase shift of 45° through the quarter-wave plate 24, passes through the spot on the disk 23, is transmitted through the polarization beam splitter 22, and is imaged by the image sensor 28 through the imaging lens 27. By driving the motor 29 through the computer 32, the entire surface of the specimen 33 can be scanned. In this case, the position where the intensity of light of a confocal image of the specimen 33 imaged by the image sensor 28 becomes ultimate is found while shifting the driving mechanism 30 or 31 along the optical axis. Whereby, the height of the specimen is detected.

The magnification of the confocal optical system 25 can also be changed in accordance with the size of the specimen 33.

In this height measuring apparatus also, the confocal optical system 25 is both-side telecentric so that even when the magnification is changed, the conjugate length remains unchanged. Therefore, there is no need to adjust the positions of individual members. Since the fluctuation of the image-side F-number is minimized and a loss of the amount of light is reduced, the adjustment of brightness is unnecessary.